



Composition:

- Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
- Reinforcement: four braids of steel wire.
- Cover: synthetic rubber, resistant to oil, abrasion and weather.

Working temperature: From -40° C to +100° C.

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MS456912	3/4"	19,0	31,5	420	6.090	1.680	24.360	280	1,70
MS456916	1"	25,2	38,5	380	5.510	1.520	22.040	340	2,50
MS456920	1"1/4	32,2	45,2	350	5.075	1.400	20.300	460	3,00
MS456924	1"1/2	38,5	53,5	290	4.206	1.160	16.824	560	3,60
MS456932	2"	51,2	68,1	250	3.625	1.000	14.504	700	5,00
MDDS456912	3/4"	19,0	31,5	420	6.090	1.680	24.360	280	1,70
MDDS456916	1"	25,2	38,5	380	5.510	1.520	22.040	340	2,50
MDDS456920	1"1/4	32,2	45,2	350	5.075	1.400	20.300	460	3,00
MDDS456924	1"1/2	38,5	53,5	290	4.206	1.160	16.824	560	3,60
MDDS456932	2"	51,2	68,1	250	3.625	1.000	14.504	700	5,00