

EN 857 2SNK hose Gold - RockCover

1/1



Composition:

- Inner tube: special synthetic rubber resistant to hydraulic oil.
- Reinforcement: two braids of steel wire.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

Working temperature: From -40° C to +100° C.

FLAME RETARDANT according to ISO 8330: 2014

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Vacuum (bar)	Bending radius (mm)	Weight (kg/m)
MPK2SNK04RC	1/4"	6.6	13,4	450	6.525	1.800	26.100	-0.95	45	0.27
MPK2SNK05RC	5/16"	8.3	15	420	6.090	1.680	24.360	-0.95	60	0.31
MPK2SNK06RC	3/8"	99	17	385	5.585	1.540	22.340	-0.95	70	0.39
MPK2SNK08RC	1/2"	13	20,7	345	5.000	1.380	20.000	-0.95	90	0.52
MPK2SNK10RC	5/8"	16.4	23,6	290	4.205	1.160	16.820	-0.8	130	0.61
MPK2SNK12RC	3/4"	19.5	27,7	280	4.060	1.120	16.240	-0.8	160	0.79
MPK2SNK16RC	1"	26	35,6	200	2.900	800	11.600	-0.8	210	1.15

