

EN 856 4SH hose Gold - RockCover

1/1



Composition: · Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
· Reinforcement: four braids of steel wire.
· Cover: synthetic rubber, very high resistant to oil, abrasion and weather.

Working temperature: From -40° C to +100° C.

FLAME RETARDANT according to ISO 8330: 2014

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
ML456912RC	3/4"	19,0	32,2	420	6.090	1.680	24.360	280	1,556
ML456916RC	1"	25,4	38,7	380	5.510	1.520	22.040	340	2,087
ML456920RC	1"1/4	32,0	45,5	350	5.075	1.400	20.300	460	2.570
ML456924RC	1"1/2	38,0	53,5	290	4.205	1.160	16.820	560	3,439
ML456932RC	2"	50,8	68,1	250	3.625	1.000	14.500	700	4,903
MPK456912RC	3/4"	19,0	32,2	420	6.090	1.680	24.360	280	1,556
MPK456916RC	1"	25,4	38,7	380	5.510	1.520	22.040	340	2,087
MPK456920RC	1"1/4	32,0	45,5	350	5.075	1.400	20.300	460	2.570
MPK456924RC	1"1/2	38,0	53,5	290	4.205	1.160	16.820	560	3,439
MPK456932RC	2"	50,8	68,1	250	3.625	1.000	14.500	700	4,903

