



Composition:

- Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
- Reinforcement: four braids of steel wire.
- Cover: synthetic rubber, high resistant to oil, abrasion and weather.

Working temperature: From -40° C to +100° C.

FLAME RETARDANT according to ISO 8330: 2014

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
ML429006RC	3/8"	9,8	21,1	445	6.455	1.780	25.810	180	0,70
ML429008RC	1/2"	13,0	24,2	425	6.465	1.700	24.070	230	0,85
ML429010RC	5/8"	16,4	27,9	350	5.075	1.400	20.300	250	1,11
ML429012RC	3/4"	19,5	32	350	5.075	1.400	20.300	300	1,41
ML429016RC	1"	26,0	38,9	280	4.640	1.120	18.500	340	1,86
MPK429006RC	3/8"	9,8	21,1	445	6.455	1.780	25.810	180	0,70
MPK429008RC	1/2"	13,0	24,2	425	6.465	1.700	24.070	230	0,85
MPK429010RC	5/8"	16,4	27,9	350	5.075	1.400	20.300	250	1,11
MPK429012RC	3/4"	19,5	32	350	5.075	1.400	20.300	300	1,41
MPK429016RC	1"	26,0	38,9	280	4.640	1.120	18.500	340	1,86

