

EN 854 1TE / SAE 100 R6 Hose

1/1



Composition:

- Inner tube: special NBR rubber resistant to hydraulic oil.
- Reinforcement: one textile braid.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

Working temperature: From -40°C to +100°C

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MSB2104	1/4"	6,3	13	28	406	112	1.624	65	0,16
MSB2105	5/16"	8,2	14,5	28	406	112	1.624	80	0,24
MSB2106	3/8"	9,8	16,5	28	406	112	1.624	80	0,29
MSB2108	1/2"	12,9	20	28	406	112	1.624	100	0,39
MSB2110	5/8"	16,2	23	24	348	96	1.392	125	0,5
MSB2112	3/4"	19,2	26,5	21	304,5	83	1.203,5	150	0,6
MSB2116	1"	25	34,5	20	290	80	1.160	170	0,75
MDAB2104	1/4"	6,3	13	28	406	112	1.624	65	0,16
MDAB2105	5/16"	8,2	14,5	28	406	112	1.624	80	0,24
MDAB2106	3/8"	9,8	16,5	28	406	112	1.624	80	0,29
MDAB2108	1/2"	12,9	20	28	406	112	1.624	100	0,39
MDAB2110	5/8"	16,2	23	24	348	96	1.392	125	0,50
MDAB2112	3/4"	19,2	26,5	21	304	83	1.203,5	150	0,60
MDAB2116	1"	25	34,5	20	290	80	1.160	170	0,75