



Composition:

- Inner tube: special NBR rubber resistant to hydraulic oil.
- Reinforcement: one textile braid.
- Cover: black rubber resistant to oil, abrasion and weather.

Working temperature: From -40°C to +100°C

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MB2205	5/16"	8	14,9	68	986	272	3.944	50	0,165
MB2206	3/8"	9.5	17,3	63	913	250	3.654	60	0.2
MB2208	1/2"	12.7	20,7	58	841	230	3.364	70	0.24
MB2210	5/8"	15.9	24,9	50	725	200	2.900	90	0.33
MB2212	3/4"	19	28	45	952	180	2.610	110	0.38
MB2216	1"	25.4	35,9	40	580	160	2.320	150	0.54
MBDQ2204	1/4"	6,4	13,4	75	1.087,5	300	4.350	40	0,145
MBDQ2205	5/16"	8,0	14,9	68	986	272	3.944	50	0,165
MBDQ2206	3/8"	9,5	17,3	63	913	250	3.654	60	0,200
MBDQ2208	1/2"	12,7	20,7	58	841	230	3.364	70	0,240
MBDQ2210	5/8"	15,9	24,9	58	725	200	2.900	90	0,333
MBDQ2212	3/4"	19,0	28	45	952	180	2.610	110	0,380
MBDQ2216	1"	25,4	35,9	40	580	160	2.320	150	0,540