



Working Temperature From -40°C to +121°C

Protection factor 4:1

Composition:

- Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil.
- Reinforcement: 4-6 braids of steel wire.
- Cover: synthetic rubber, resistant to oil, abrasion and weather.

Exceeds r15

Part n°	DN	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MFLEX6012	19	3/4"	19,1	30,5	420	6.000	1.680	24.000	120	1,40
MFLEX6016	25	1"	25,4	38,1	420	6.000	1.680	24.000	150	2,01
MFLEX6020	32	1"1/4	31,8	48,6	420	6.000	1.680	24.000	240	3.65
MFLEX6024	38	1"1/2	38,1	55	420	6.000	1.680	24.000	290	4,24
MDQFLEX6012	19	3/4"	19,1	30,5	420	6.000	1.680	24.000	120	1,40
MDQFLEX6016	25	1"	25,4	38,1	420	6.000	1.680	24.000	150	2,01
MDQFLEX6020	32	1"1/4	31,8	48,6	420	6.000	1.680	24.000	240	3.65
MDQFLEX6024	38	1"1/2	38,1	55	420	6.000	1.680	24.000	290	4,24
MDQFLEX6032	51	2"	50,8	71,7	420	6.000	1.680	24.000	480	6.86