

Hot water superservice 1SC blue

1/1



Composition:

- Inner tube: synthetic rubber resistant to hydraulic, mineral and vegetable oil.
- Reinforcement: one braid of steel wire.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

Working temperature: From -40° C to +155° C (peak).

Part n°	DN	Ø in	Ø out	Working Pressure (bar)	Working pressure (psi)	Burst pressure (bar)	Burst pressure (psi)	Bending radius (mm)	Weight (kg/m)
MSC0114A	1/4"	6,5	13,2	225	3.263	900	13.050	75	0,12
MSC0115A	5/16"	8,1	14,2	215	3.118	860	12.470	85	0,14
MSC0116A	3/8"	9,7	16	180	2.610	720	10.440	90	0,19
MSC0118A	1/2"	12,9	19,2	160	2.320	640	9.280	130	0,22
MDDSC0114A	1/4"	6,5	13,2	225	3.263	900	13.050	75	0,12
MDDSC0115A	5/16"	8,1	14,2	215	3.118	860	12.470	85	0,14
MDDSC0116A	3/8"	9,7	16	180	2.610	720	10.440	90	0,19
MDDSC0118A	1/2"	12,9	19,2	160	2.320	640	9.280	130	0,22