

**Hot water superservice 2SC grey**

1/1



**Composition:** ·Inner tube: special synthetic rubber resistant to mineral, vegetable and hydraulic oil. ·Reinforcement: two braids of steel wire. ·Cover: synthetic rubber resistant to oil, abrasion and weather.

**Working temperature:** From -40° C to +155° C (peak).

| Part n°           | DN    | Ø in | Ø out | Working Pressure (bar) | Working pressure (psi) | Burst pressure (bar) | Burst pressure (psi) | Bending radius (mm) | Weight (kg/m) |
|-------------------|-------|------|-------|------------------------|------------------------|----------------------|----------------------|---------------------|---------------|
| <b>MSC0205G</b>   | 5/16" | 8.3  | 14,6  | 400                    | 5.800                  | 1.400                | 20.300               | 85                  | 0,30          |
| <b>MSC0206G</b>   | 3/8"  | 9.9  | 16,6  | 400                    | 5.800                  | 1.320                | 23.200               | 90                  | 0,37          |
| <b>MDDSC0205G</b> | 5/16" | 8.3  | 14,6  | 400                    | 5.800                  | 1.400                | 20.300               | 85                  | 0,30          |
| <b>MDDSC0206G</b> | 3/8"  | 9.9  | 16,6  | 400                    | 5.800                  | 1.320                | 20.300               | 90                  | 0,37          |