

**Hot water superservice 2ST blue**

1/1



**Composition:**

- Inner tube: special synthetic rubber resistant to hydraulic oil.
- Reinforcement: two braids of steel wire.
- Cover: synthetic rubber resistant to oil, abrasion and weather.

**Working temperature:** From -40° C to +155° C (peak).

| Part n°           | DN    | Ø in | Ø out | Working Pressure (bar) | Working pressure (psi) | Burst pressure (bar) | Burst pressure (psi) | Vacuum (bar) | Bending radius (mm) | Weight (kg/m) |
|-------------------|-------|------|-------|------------------------|------------------------|----------------------|----------------------|--------------|---------------------|---------------|
| <b>MSC0225A</b>   | 5/16" | 8,1  | 19    | 350                    | 5.075                  | 1.400                | 20.300               | -0,95        | 115                 | 0,45          |
| <b>MSC0226A</b>   | 3/8"  | 9,8  | 21,2  | 330                    | 4.785                  | 1.320                | 19.140               | -0,95        | 130                 | 0,54          |
| <b>MDDSC0225A</b> | 5/16" | 8,1  | 19    | 350                    | 5.075                  | 1.400                | 20.300               | -0,95        | 115                 | 0,45          |
| <b>MDDSC0226A</b> | 3/8"  | 9,8  | 21,2  | 330                    | 4.785                  | 1.320                | 19.140               | -0,95        | 130                 | 0,54          |