

STANDARD SERIES FITTINGS

Conexiones Serie Standard
Armaturen Standardserie
Embouts série Standard

3000 PSI SAE Straight Flange / Code 61

Brida recta SAE 3000 PSI

Gerader Flansch SAE 3000 PSI

Bride SAE droite série 3000 PSI



DN	Ø Ø	Part n° Referencia	€
1/2"	30,2	241820808	*
1/2"	38,1	241821208	*
5/8"	38,1	241821210	*
3/4"	38,1	241821212	*
3/4"	44,5	241821612	*
1"	44,5	241821616	*
1"	50,8	241822016	*
1"1/4	50,8	241822020	*
1"1/4	60,3	241822420	*
1"1/2	60,3	241822424	*
1"1/2	71,4	241823224	*
2"	71,4	241823232	*
2" 1/2	84,1	241824040	*
3"	101,6	241824848	*

3000 PSI SAE Flange (90° Elbow) / Code 61

Brida a 90° SAE 3000 PSI

Flansch 90° SAE 3000 PSI

Bride SAE coude 90° série 3000 PSI



DN	Ø Ø	Part n° Referencia	€
1/2"	30,2	241830808	*
1/2"	38,1	241831208	*
5/8"	38,1	241831210	*
3/4"	38,1	241831212	*
3/4"	44,5	241831612	*
1"	44,5	241831616	*
1"	50,8	241832016	*
1"1/4	50,8	241832020	*
1"1/4	60,3	241832420	*
1"1/2	60,3	241832424	*
1"1/2	71,4	241833224	*
2"	71,4	241833232	*

3000 PSI SAE Flange (45° Elbow) / Code 61

Brida a 45° SAE 3000 PSI

Flansch 45° SAE 3000 PSI

Bride SAE coude 45° série 3000 PSI



DN	Ø Ø	Part n° Referencia	€
1/2"	30,2	241840808	*
1/2"	38,1	241841208	*
5/8"	38,1	241841210	*
3/4"	38,1	241841212	*
3/4"	44,5	241841612	*
1"	44,5	241841616	*
1"	50,8	241842016	*
1"1/4	50,8	241842020	*
1"1/4	60,3	241842420	*
1"1/2	60,3	241842424	*
1"1/2	71,4	241843224	*
2"	71,4	241843232	*

6000 PSI SAE Straight Flange / Code 62

Brida recta SAE 6000 PSI

Gerader Flansch SAE 6000 PSI

Bride SAE droite série 6000 PSI



DN	Ø Ø	Part n° Referencia	€
1/2"	31,8	242820808	*
1/2"	41,3	242821208	*
5/8"	41,3	242821210	*
3/4"	41,3	242821212	*
3/4"	47,6	242821612	*
1"	47,6	242821616	*
1"	54	242822016	*
1"1/4	54	242822020	*
1"1/4	63,5	242822420	*
1"1/2	63,5	242822424	*
1"1/2	79,4	242823224	*
2"	79,4	242823232	*

6000 PSI SAE Flange (90° Elbow) / Code 62

Brida a 90° SAE 6000 PSI

Flansch 90° SAE 6000 PSI

Bride SAE coude 90° série 6000 PSI



DN	Ø Ø	Part n° Referencia	€
1/2"	31,8	242830808	*
1/2"	41,3	242831208	*
5/8"	41,3	242831210	*
3/4"	41,3	242831212	*
3/4"	47,6	242831612	*
1"	47,6	242831616	*
1"	54	242832016	*
1"1/4	54	242832020	*
1"1/4	63,5	242832420	*
1"1/2	63,5	242832424	*
1"1/2	79,4	242833224	*
2"	79,4	242833232	*

6000 PSI SAE Flange (45° Elbow) / Code 62

Brida a 45° SAE 6000 PSI

Flansch 45° SAE 6000 PSI

Bride SAE coude 45° série 6000 PSI



DN	Ø Ø	Part n° Referencia	€
1/2"	31,8	242840808	*
1/2"	41,3	242841208	*
5/8"	41,3	242841210	*
3/4"	41,3	242841212	*
3/4"	47,6	242841612	*
1"	47,6	242841616	*
1"	54	242842016	*
1"1/4	54	242842020	*
1"1/4	63,5	242842420	*
1"1/2	63,5	242842424	*
1"1/2	79,4	242843224	*
2"	79,4	242843232	*

STANDARD SERIES FITTINGS

Conexiones Serie Standard
Armaturen Standardserie
Embouts série Standard

9000 PSI straight Flange (14,3)

Brida recta 9000 PSI (14,3)

Gerader Flansch SAE 9000 PSI (14,3)

Bride tournante droite série 9000 PSI (14,3)



9000 PSI 90° Flange (14,3)

Brida a 90° 9000 PSI (14,3)

Flansch 90° SAE 9000 PSI (14,3)

Bride tournante coude 90° série 9000 PSI (14,3)



DN	Ø Ø	Part n° Referencia	€
3/4"	41,3	442821212	*
3/4"	47,6	442821612	*
1"	47,6	442821616	*
1"	54	442822016	*
1" 1/4	54	442822020	*
1" 1/2	63,5	442822424	*

DN	Ø Ø	Part n° Referencia	€
3/4"	41,3	442831212	*
3/4"	47,6	442831612	*
1"	47,6	442831616	*
1"	54	442832016	*
1" 1/4	54	442832020	*
1" 1/2	63,5	442832424	*

9000 PSI 45° Flange (14,3)

Brida a 45° 9000 PSI (14,3)

Flansch 45° SAE 9000 PSI (14,3)

Bride tournante coude 45° série 9000 PSI (14,3)



DN	Ø Ø	Part n° Referencia	€
3/4"	41,3	442841212	*
3/4"	47,6	442841612	*
1"	47,6	442841616	*
1"	54	442842016	*
1" 1/4	54	442842020	*
1" 1/2	63,5	442842424	*