

FITTINGS BW+ SERIES R13/R15 NO SKIVE

Conexiones Serie BW+ R13/R15 No Pelar
Armaturen Serie BW+ R13/R15 ohne Schälung
Embouts R13/R15 Série BW+ Sans denuder

6000 PSI SAE Straight flange

Brida recta SAE 6000 PSI

Gerader Flansch SAE 6000 PSI

Bride SAE droite série 6000 PSI



DN	Ø	Part n° Referencia	€
1" 1/4	54	662822020	*
1" 1/2	63.5	662822424	*
2"	79.4	662823232	*

6000 PSI SAE 90° Flange

Brida a 90° SAE 6000 PSI

Flansch 90° SAE 6000 PSI

Bride SAE coude 90° série 6000 PSI



DN	Ø	Part n° Referencia	€
1" 1/4	54	662832020	*
1" 1/2	63.5	662832424	*
2"	79.4	662833232	*

6000 PSI SAE 45° flange

Brida a 45° SAE 6000 PSI

Flansch 45° SAE 6000 PSI

Bride SAE coude 45° série 6000 PSI



DN	Ø	Part n° Referencia	€
1" 1/4	54	662842020	*
1" 1/2	63.5	662842424	*
2"	79.4	662843232	*

ORFS Swivel female straight double hexagonal

Hembra giratoria recta ORFS asiento plano doble hexagonal

Dichtkopf gerade ORFS flachdichtend doppelt 6 kt

Femelle droite ORFS double hexagonale



DN	THREAD ROSCA	Part n° Referencia	€
1" 1/4	1" 11/16 12h UNF	669012020	*
1" 1/2	2" 12h UNF	669012424	*

ORFS Swivel female (90° Elbow)

Hembra giratoria 90° ORFS asiento plano

Dichtkopf mit Ü-Mutter ORFS 90° flachdichtend

Coude 90° femelle ORFS



DN	THREAD ROSCA	Part n° Referencia	€
1" 1/4	1" 11/16 12h UNF	669072020	*
1" 1/2	2" 12h UNF	669072424	*

ORFS Swivel female (45° Elbow)

Hembra giratoria 45° ORFS asiento plano

Dichtkopf mit Ü-Mutter ORFS 45° flachdichtend

Coude 45° femelle ORFS



THREAD ROSCA	Part n° Referencia	€
1" 11/16 12h UNF	669082020	*
2" 12h UNF	669082424	*